


Insulated Panels  
Hungary

# Kingspan KS1150 RB-L

## Wall panel

## Product datasheet



# Product Data


## Application

The KS1150 RB-L is a through-fixed wall system which can be laid vertically or horizontally and it is suitable for wall cladding on all types of buildings except where there are internal low temperature conditions (below 0 °C).


Panel RB-L available also in module 1000mm as KS1000 RB-L.\*\*

The application of panel should be verified for each project individually, in order to meet the design requirements.

\*\* see in a separate datasheet



## Dimensions



## Technical parameters

| Width [mm]          | Core thickness D [mm] | Weight [kg/m²]                                             | Length of the panels [m] |                      | Number of panels in package [pcs] | Insulation U-value [W/m²K]<br>$\lambda = 0,044 \text{ W/mK}$<br>at temp. 10°C | Single figure weighted sound reduction $R_w$ [dB] |
|---------------------|-----------------------|------------------------------------------------------------|--------------------------|----------------------|-----------------------------------|-------------------------------------------------------------------------------|---------------------------------------------------|
|                     |                       | Thickness of steel facings external/internal 0,6 mm/0,5 mm | Minimum <sup>(1)</sup>   | Maximum              |                                   |                                                                               |                                                   |
| 1150 <sup>(2)</sup> | 60                    | 17,30                                                      | 2,00                     | 7,00                 | 17                                | 0,70                                                                          | N/A                                               |
|                     | 80                    | 19,60                                                      |                          | 9,00                 | 13                                | 0,52                                                                          |                                                   |
|                     | 100                   | 21,90                                                      |                          | 16,00 <sup>(3)</sup> | 10                                | 0,42                                                                          |                                                   |
|                     | 120                   | 24,20                                                      |                          |                      | 8                                 | 0,35                                                                          |                                                   |
|                     | 150                   | 27,70                                                      |                          |                      | 6                                 | 0,29                                                                          |                                                   |
|                     | 175                   | 30,50                                                      |                          |                      | 6                                 | 0,25                                                                          |                                                   |
|                     | 200                   | 33,40                                                      |                          |                      | 5                                 | 0,22                                                                          |                                                   |

<sup>(1)</sup> At the request of the ordering party (for an additional fee) it is possible to deliver shorter panels. In other cases, short sections are combined in length meeting the production requirements.

<sup>(2)</sup> Panel available also in module width 1000 mm.

<sup>(3)</sup> Max recommended length 9,0m. For longer panels there is a risk of panel damage during delivery or manipulation.

# Product Data

## Steel

### Galvanic protection options

- Hot-dip zinc coated steel with a total of 275 g/m<sup>2</sup> of zinc or equivalent, according to EN10147:2000. This can be finished with different coatings - Polyester(PES), Spectrum™ and Foodsafe.
- Hot-dip zinc coated steel with a total of 100 g/m<sup>2</sup> of zinc, according to EN10147:2000. This can be finished with a 15µm Polyester (PEI) coating. (Standard internal face)

### Substrate thicknesses

- Standard external sheet thickness 0,6 mm
  - Standard internal sheet thickness 0,5 mm
- Other thicknesses are available by arrangement with Kingspan.

## Coating

### Coatings – External Weather Sheet

- Standard Polyester - PES  
Polyester is a universal, economic coating system suitable for exterior and interior applications. The nominal coating thickness is 25 µm. This coating is suitable for both external and indoor applications with C1-C3 corrosion environment class (EN10169)
- PVDF  
PVDF offers unequalled colour and gloss retention and good corrosion resistance. The nominal coating thickness is 25-35 µm. This coating is suitable for both external and indoor applications with C1-C4 corrosion environment class (EN10169).The standard colour range includes metallic silver.
- Spectrum™  
Kingspan Spectrum™ is a 50 µm Polyurethane coated semi gloss finish with a slight granular effect. It offers an outstanding durability and weather resistance performance, excellent corrosion and UV resistance as well as high color & gloss retention characteristics. This coating is suitable for both external and indoor applications with C1-C5 corrosion environment class (EN10169). Its superior flexibility enables high resistance against mechanical damages. Kingspan Spectrum is available in a wide range of solid and metallic colours. Furthermore it is free of chlorine, phthalates and plasticizers and 100% recyclable.

### Coatings – Internal Liner Sheet

- Thin Coating – PEI  
Polyester coating with a nominal thickness of 15 µm. The standard colour is grey white (similar RAL 9002). This coating is suitable only for indoor applications with C1-C2 corrosion environment class (EN10169).
- Polyester – PES  
Polyester is a universal, economic coating system suitable for exterior and interior applications. The nominal coating thickness is 25 µm. This coating is suitable for both external and indoor applications with C1-C3 corrosion environment class (EN10169).

## Fire

| Core thickness D [mm] | Reaction to fire | Fire resistance                                                |                                            |
|-----------------------|------------------|----------------------------------------------------------------|--------------------------------------------|
|                       |                  | Horizontal                                                     | Vertical                                   |
| 60                    | A2-s1, d0        | EI15 - 4,00m                                                   | EI15 - 4,00m                               |
| 80                    |                  |                                                                |                                            |
| 100                   |                  | EI90/EW120 - 7,50m<br>EI120/EW180 - 4,00m                      | EI90/EW120 - 7,50m<br>EI120/EW120 - 3,00m  |
| 120                   |                  |                                                                |                                            |
| 150                   |                  | EI120/EW120-7,50m<br>EI20/EW180 - 6,00m<br>EI180/EW240 - 3,00m | EI120/EW180 - 7,50m<br>EI180/EW240 - 3,00m |
| 175                   |                  |                                                                |                                            |
| 200                   |                  |                                                                |                                            |

## Biological

Kingspan insulated sandwich panels are immune to attack from mould, fungi, mildew and vermin. No urea formaldehyde is used in the construction, and the panels are non-deleterious.

## Seals

### Factory Applied Side Joint Tape

All KS1150 RB-L panel side joints have factory applied anti-condensation seals fitted into the groove to automatically seal the joint between panels.

## Building Regulations

Kingspan KS1150 RB-L insulated sandwich panels apply to the european standard EN 14509:2013 Self-supporting double skin metal faced insulating panels and conform to additional National Building Regulations and standards.

## Quality

Kingspan insulated sandwich panels are manufactured from the highest quality materials, using state of the art production equipment to rigorous quality control standards, complying with ISO 9001:2015 standards, ensuring long term reliability and service life. KS1150 RB-L sandwich panels are manufactured in accordance with the EN 14 509 and CE marked.

## Guarantees & Warranties

The Kingspan guarantees are individually assessed for each project, especially depending on the aggressiveness of the environment and the type of surface treatment chosen.

## Delivery


All deliveries (unless indicated otherwise) are by road transport to project site. Off loading is the responsibility of the client.

## Site Installation


Site assembly instructions are available from Kingspan. Kingspan will arrange training of the site fitters and supervisors if requested

# Profilation

## External facing profiles



## Internal facing profiles





Kingspan Kereskedelmi Kft.  
Horka dűlő 1. | H-2367 Újhartyán

T: +36 30 455 4021  
E: ajanlat@kingspan.hu  
www.kingspan.hu


Information about the product offer in other countries can be obtained from your local sales representative or on the website: [www.kingspan.com](http://www.kingspan.com)

Although Kingspan makes every effort to provide information contained in this publication as accurate as possible, correct and complete, please note that its content should not be the basis of the procedure in any particular case. Any advice, opinions, information or other content is published solely based on the principle that neither the company, its employees or representatives, or people who contributed to the uprising of this publication, do not assume any liability for its content or any damage caused in connection with this content.

Datasheet updated: 23/02/2023



# PLANET PASSIONATE



In Autumn 2021, we launched Planet Passionate Communities, the philanthropic arm of our ambitious 10-year sustainability programme, Planet Passionate. Through our Planet Passionate Communities initiative, we are striving to support people and communities around the world while promoting sustainable practices using responsibly sourced materials.

Our Planet Passionate Communities initiative is having both a local and global impact. On a local level, our businesses are devoting their time and resources to support community projects. By creating a local impact, we aspire to build a world that is powered by renewable energy, net-zero carbon, manages water sustainably, and protects the earth's valuable resources by reducing, re-using and recycling.

On a global level, we have joined forces with GOAL, the international humanitarian response agency, to develop critical infrastructure with sustainability at its core, in healthcare and education.

At the core of our Planet Passionate Communities initiative is the ambition to create a positive legacy and a better world. By forging a local legacy, here, at Kingspan, we are determined to use our expertise to create positive impacts for people and communities internationally, and to advance the sustainability agenda for all.

Climate change is the single most important issue facing the world today. To protect our planet, we need to prevent a 1.5° rise in global temperatures this century. To do this, carbon emissions need to be cut to net zero globally by 2050 – but we are currently on course to miss this goal by at least five-fold.



POWERED BY  
**QuadCore**  
TECHNOLOGY